

There are 4 Types of Shortcodes :

1) Basic Shortcode :

[queryword parameter="keyword" default="my word" capitalization="no"]

Example URL : www.domain.com/test-page/?keyword=MyQueryValue

Printed value : MyQueryValue

2) Anchor Shortcode :

It has 3 methods (insertfor) based on your anchor structure –

(a) For Anchor text : [insertanchor parameter="keyword" default="hello" href="http://pixelsigns.com/" anchortext="Click Here" insertfor="hreftext"]

Example URL : www.domain.com/test-page/?keyword=Anchor Text

It will execute as HTML : Anchor Text

(b) For Anchor Link : [insertanchor parameter="keyword" default="hello" href="http://pixelsigns.com/" anchortext="Click Here" insertfor="anchorlink"]

Example URL : www.domain.com/test-page/?keyword=http://google.com

It will execute as HTML : Click Here

(c) For Appending URL : [insertanchor parameter="keyword" default="hello" href="http://pixelsigns.com/" anchortext="Click Me" insertfor="appendurl"]

Example URL : www.domain.com/test-page/?keyword=AppendThisValue

It will execute as HTML : Click Me

3) For INPUT field Shortcode :

Two types of INPUT Text (value) can create : Input field, Hidden Input field

(a) For Input type TEXT Field: [insertfield parameter="keyword" default="hello" type="text" class="testClass" id="fieldID" name="insertfield"]

Example URL : www.domain.com/test-page/?keyword=InputFieldValue

It will execute as HTML : <input type="text" name="insertfield" class=" testClass " id="fieldID" value="InputFieldValue">

(b) For Hidden Field Value : [insertfield parameter="keyword" default="hello" type="hidden" class="testClass" id="fieldID" name="insertfield"]

Example URL : www.domain.com/test-page/?keyword=HiddenValue

It will execute as HTML : <input type="hidden" name="insertfield" class="testClass" id="fieldID" value="HiddenValue">

4) Shortcode for URL SLUG :

[getslug queryslug="services" default="hello world"]

Example URL : www.domain.com/services/client-support

Printed value : client-support

This plugin allows user to display (print) value from URL parameter or slug in some sort of ways. Simply, we can say this plugin has option to grab the keyword value from URL parameter (address bar) and print them inside page, post, title or widgets.

Besides, plugin has 4 types of shortcode to cover all types of usability.

- 1) Print Value from Query String (Keyword Parameter) to any heading tag, title, body text or widegts.
- 2) Create dynamic ANCHOR (link) with 3 different positions. See details .
- 3) Create html INPUT tag (text & hidden field) to place value from Keyword Parameter.
- 4) Grab the slug value after certain word from URL.

No complex method, easy to use and option to print default value.

 - If the VALUE available against keyword it will present as a TEXT where the shortcode is set.

 -> If no VALUE found from URL parameter, DEFAULT value will be placed.

<h3>

</h3>

<h3>KEY Features at a glance:</h3>

4 types of Shortcode Enable to server all types of usabilities.

Visual Composer Supported

Any keyword can be used for query string (parameter)

Can set anywhere in Title, Body Content, Widgets etc

Have option to enable/disable for adword capitalization

Organic search query (from Google, Yahoo, Bing) enabled

Default TEXT can be placed if no keyword found.